

For a handicap bathroom, the minimum dimensions for a wheelchair-accessible stall are 60 inches wide and 56 inches deep, with a 32-inch wide door, and a 60-inch diameter turning space.

Here's a more detailed breakdown of ADA-compliant handicap bathroom dimensions:

General Space Requirements:

- **Minimum Room Size:** A minimum of 60 inches wide by 56 inches deep, plus clearance space for fixtures.
- **Turning Space:** A 60-inch diameter circular or a 60-inch T-shaped area is required for wheelchair maneuvering.
- **Door Clearance:** The clear width of a door opening must be a minimum of 32 inches.
- **Door Swing:** Doors should swing outwards or be equipped with a self-closing mechanism.
- **Clear Floor Space:** A clear floor space of 12 inches is required on the push side of the door, and 18 inches on the pull side for a front approach.

Toilet Compartment:

- **Width:** At least 60 inches.
- **Depth:** At least 56 inches for wall-hung toilets, or 59 inches for floor-mounted toilets.
- **Toilet Seat Height:** 17 inches to 19 inches from the floor.
- **Grab Bars:**
 - **Placement:** Located on the side wall (at least 54 inches long) and the rear wall (at least 42 inches long).
 - **Height:** Between 33-36 inches above the floor.
- **Clearance:** A minimum of 60 inches measured perpendicular from the sidewall and 56 inches measured perpendicular from the rear wall.

Sink:

- **Height:**

The sink should be mounted so that the bottom edge of the basin is no higher than 34 inches from the floor.
- **Clearance:**

There should be a clear area underneath the sink, free of obstructions, to allow for wheelchair access.

Important Considerations:

- **Compliance:**

These dimensions are based on the [Americans with Disabilities Act \(ADA\)](#) standards.

